

B  **2**

OXYGEN
CYLINDER



B₂

OXYGEN
CYLINDER

INDUSTRIAL SPECIALTY GAS CYLINDERS

Aluminum gas cylinders are ideal to store industrial and specialty gases because of light weight, non-magnetism, and corrosion resistance.



SPECIFICATIONS

SALE CODE	Water Capacity	Outside Diameter	Overall Length	Wall Thickness	Empty Weight	Working Pressure	
	Lts.	mm.	mm.	mm.	kgs.	bar	psi
S60-1	0.5	60	285	3.1	0.59	150	2176
S89-1	0.6	89	210	4.5	0.94	150	2176
S73-1	0.7	73	276	3.7	0.81	150	2176
S81-2	0.8	81	248	4.1	0.80	150	2176
S81-3	1.0	81	296	4.1	0.93	150	2176
S111-1	1.4	111	270	5.6	2.04	150	2176
S111-2	1.7	111	310	5.6	2.28	150	2176
S108-1	2.0	108	360	5.6	2.26	150	2176
S111-3	2.3	111	389	5.6	2.75	150	2176
S108-2	2.5	108	428	5.6	2.62	150	2176
S120-3	2.8	120	400	6.1	3.03	150	2176
S120-4	3.2	120	438	6.1	3.38	150	2176
S133-1	4.0	133	429	6.7	3.58	150	2176
S140-2	5.0	140	505	7.1	5.20	150	2176
S176-1	5.9	176	435	8.9	7.87	150	2176
S140-3	6.0	140	590	7.1	5.90	150	2176
S140-4	7.0	140	675	7.1	6.60	150	2176
S176-2	7.5	176	512	8.9	9.05	150	2176
S140-5	8.0	140	755	7.1	7.12	150	2176
S133-2	8.4	133	821	6.7	6.42	150	2176
S176-3	8.5	176	560	8.9	9.79	150	2176
S176-4	9.4	176	603	8.9	10.50	150	2176
S159	10.0	159	740	8.1	8.98	150	2176
S184-2	10.7	184	625	9.3	11.90	150	2176
S203-1	12.0	203	600	10.3	14.10	150	2176
S203-2	13.4	203	650	10.3	13.90	150	2176
S176-6	13.5	176	800	8.9	13.50	150	2176
S184-3	15.0	184	831	9.3	15.20	150	2176
S184-4	15.7	184	865	9.3	15.8	150	2176
S203-4	20.0	203	910	10.3	18.90	150	2176
S203-5	21.3	203	962	10.3	19.90	150	2176
S232-1	29.5	232	994	11.7	30.20	150	2176
S232-2	30.0	232	1010	11.7	30.50	150	2176
S232-3	31.5	232	1060	11.7	31.40	150	2176
S232-4	35.0	232	1175	11.7	33.50	150	2176
S232-5	40.0	232	1340	11.7	36.50	150	2176
S250-1	46.4	250	1316	12.6	39.30	150	2176
S250-2	47.5	250	1343	12.6	40.00	150	2176

SALE CODE	Water Capacity	Outside Diameter	Overall Length	Wall Thickness	Empty Weight	Working Pressure	
	Lts.	mm.	mm.	mm.	kgs.	bar	psi
S73-2	0.5	73	220	4.90	0.81	200	2901
S73-3	0.6	73	255	4.90	0.92	200	2901
S102-1	1.0	102	227	6.80	1.45	200	2901
S102-2	2.0	102	390	6.80	2.36	200	2901
S120-5	2.0	120	344	8.00	3.37	200	2901
S111-4	3.0	111	488	7.40	3.92	200	2901
S140-6	4.0	140	478	9.30	6.01	200	2901
S140-7	5.0	140	565	9.30	7.00	200	2901
S152-1	5.0	152	466	10.10	6.23	200	2901
S184-5	9.5	184	598	12.20	12.40	200	2901
S176-7	10.0	176	642	11.70	12.10	200	2901
S184-6	10.0	184	620	12.20	12.90	200	2901
S203-6	10.0	203	550	13.40	14.90	200	2901
S184-7	12.0	184	710	12.20	14.80	200	2901
S203-7	12.0	203	630	13.40	16.70	200	2901
S203-8	13.4	203	686	13.40	18.00	200	2901
S203-9	15.0	203	750	13.40	19.50	200	2901
S232-8	20.0	232	731	15.40	25.00	200	2901
S232-9	26.0	232	951	15.40	30.70	200	2901
S232-10	31.5	232	1096	15.40	36.00	200	2901
S232-11	40.0	232	1365	15.40	44.10	200	2901
S250-1	50.0	250	1503	16.50	54.90	200	2901

* For more working pressures and other specifications please contact us.

B₂

OXYGEN
CYLINDER

